



ECOGLUE™ EXTREME is a high performance polyether moisture cure technology that is 100% solids, solvent free and less than 2% VOC.

It's engineered for strong adhesion to virtually any substrate, and will provide a long lasting weather tight seal even in the most unfavorable wet application conditions. EcoGlue Extreme is suitable for vertical or overhead applications and can be painted after 24 hours. It is safe to use indoors,

or in confined spaces, as it contains no odor. Best application

temperatures are above 30 F (-1 C).



EXTREME

PREMIUM ADHESIVE & SEALANT

Moisture Cure / Odor Free / Non-Shrink / Instant Grab / Flexible / Waterproof / Paintable



**Environmentally Friendly
Without Sacrificing
Strength.
Multiple Applications.
Provides Maximum
Performance.**



This product may help a LEED® project earn a point in the Indoor Environmental Quality category for the LEED certification process.



Product Benefits	Substrates
Moisture Cure Technology	Concrete
100% Solids/Non Shrink or Crack	Block
No Solvents/No Outgassing	Brick
Less than 2% VOC	Stone
No Prop 65 Materials	Wood
No Odor	Cement Fiber Board
Non-Sag/Applies Vertically & Horizontally	Masonry (bonds to damp masonry)
Instant Grab	Galvanized Metal
Elastic/Flexible	Aluminium
No Mixing-Single Component	PVC
Waterproof	SBS Mod Bit
Excellent Weathering Properties	EPDM
Provides Temporary Emergency Underwater Repair	Many Engineering Plastics
Formaldehyde Free	Vinyl
UV Stable	Glass
Paintable	Foam
Dries White	& More

Best application temperatures are above 30° F.
Withstands temperatures from -40° F to 200° F after full cure. Freeze/thaw stable.

EXTREME

PREMIUM ADHESIVE & SEALANT



Industry Uses

- Truck/Bus/Metro/RV
- Manufactured Housing
- Construction (Residential/Commercial)
- Light Trailers
- Metal Buildings
- Steel Roofing
- Steel Entry Doors

EcoGlue™ Extreme	Sales Part	Item UPC	Case Weight	Case Dimensions	Case Cube
EcoGlue Extreme 10.1 oz	575012	0 76818 75012 3	15 lbs	7.94 x 5.94 x 11.25	.31 ft ³

196A 4/08

For more information contact Glu Guru at 1-800-323-5158

