



1001 Trout Brook Crossing  
Rocky Hill, CT 06067-3910  
Telephone: (860) 571-5100  
FAX: (860) 571-5465

## Product Description Sheet Hysol® 050 Hot Melt Applicator

Part # 98544 120 VAC; 50/60 Hz.

Part # 98546 230 VAC; 50/60 Hz.

North American Engineering Center, September 2005

### PRODUCT DESCRIPTION

The newly improved Loctite® Hysol® 050 Hot Melt Applicator is a lightweight hand-held, Hot Melt adhesive applicator. With a new high performance PTFE inlet tube you can now count on longer term, reliable dispensing performance. Ergonomic comfort grip makes easy dispensing of any Loctite® Hysol® EVA Hot Melt Superstick™ in any industrial production environment.

### PRODUCT FEATURES

- Designed for operator comfort and application control
- Rugged feed tube design ensures long term reliability
- Low actuation force to reduce finger fatigue
- Electronic temperature control
- Dispenses up to 3.0 pounds per hour
- Adhesive: 1/2 inch diameter EVA Supersticks™.

### Technical Data

- Weight 1.50 pounds
- Dimensions: 10 ¼ L x 7 ½ H x 3 W
- Electrical cord length: 78 "
- Power requirements:
  - # 98544 120 VAC; 50/60 Hz.
  - # 98546 230 VAC; 50/60 Hz.
- Power consumption: 250 watts
- Fixed precision temperature setting 383°F (195°C)
- Heat-up time: 4 to 5 minutes



### Hot Melt Stick Applicator includes

- Hysol 050 Hot Melt Stick Applicator
- Instruction Manual – P/N 989430
- Wire Hanger – P/N 985182
- Dispenser Stand – P/N 985181
- Standard 1-hole nozzle; .06" DIA. Tip – P/N 988108
- Adapter / check valve for nozzles – P/N 988107

### Optional Accessories (not included):

- 2-hole nozzle – P/N 985110
- 3-hole nozzle – P/N 985111
- Extension nozzle; .14" DIA. X 1.23" LG – P/N 985112
- Needle extension nozzle; .05" DIA. X 1.32" LG – P/N 985113
- Spreader extension nozzle; .09" .25" SQ. x 1.22" LG – P/N 985114
- "L" Nozzle (ideal for overlap carton sealing) – P/N 985115
- "T" Nozzle (ideal for overlap carton sealing) – P/N 985116

NOT FOR PRODUCT SPECIFICATIONS

Loctite is a TM of Henkel Corporation, U.S.A. © Copyright 2004. Henkel Corporation. All rights reserved

